



Characteristic Curves

THM 20-1211


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




THM 20-1212


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-1213


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-1215


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-1221


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-1222


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-1223


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2411


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2412


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2413


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2415


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2421


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2422


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-2423


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4811


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4812


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4813


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4815


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4821


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4822


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THM 20-4823


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)



Typical Start-Up and Output Rise Characteristic



Remote on/off Voltage Start-Up Characteristic

