



Ref. Certif. No.

**SI-8373**

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

**CB TEST CERTIFICATE**

Product

Power supply for built-in use

Name and address of the applicant

Traco Power Solutions Ltd.  
Whitemill Industrial Estate Wexford, White Mill Road,  
Y35 YH66, Ireland

Name and address of the manufacturer

Traco Power Solutions Ltd.  
Whitemill Industrial Estate Wexford, White Mill Road,  
Y35 YH66, Ireland

Name and address of the factory

Traco Power Solutions Ltd.  
Whitemill Industrial Estate Wexford, White Mill Road,  
Y35 YH66, Ireland*Note: When more than one factory, please report on page 2* Additional Information on page 2

Ratings and principal characteristics

See page 2

Trademark / Brand (if any)

TRACO POWER

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

See page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN 62368-1:2014 + A11:2017;  
National Differences specified in the CB Test Report. Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0608/20 (2020-10-06)

This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia  
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2020-10-06

Signature: Bojan Pečavar

**Models:**

TOP 200-112 or 200HPP182  
TOP 200-115 or 200HPP183  
TOP 200-124 or 200HPP184  
TOP 200-148 or 200HPP185  
S200HPP1UV48 or S200HPP1UV48

Each model can be alternatively marked with the suffix "C" for optional casing.

Models can be additionally marked with xxxxxxxx, where 'x' or 'a' can be any alphanumeric, blank or dash, no impact on safety

**Ratings and principal characteristics:**

Input: 120-240 Vac; 50/60 Hz; 2-1 A

Output:

TOP 200-112 or 200HPP182: 12 Vdc; 16 A  
TOP 200-115 or 200HPP183: 15 Vdc; 13 A  
TOP 200-124 or 200HPP184: 24 Vdc; 8,3 A  
TOP 200-148 or 200HPP185: 48 Vdc; 4,2 A  
S200HPP1UV48 or S200HPP1UV48: 48 Vdc; 4,2 A

**Additional information (if necessary)**

Date: 2020-10-06

Signature: Bojan Pečavar

